

SPECIFICATIONS



Species: Pinus strobus

Common Names: Eastern White pine

Brand/Trade Name: Primelock®

Range Of Origin: Maine; northeast US; eastern Quebec

Appearance: Uniform texture. Straight-grained. Naturally light in color. Accepts paint well.

Grade: Clear

Patterns: Center Match 1x6
Chair Rail Patterns (2)
Edge & Center Bead: 5/8x4, 5/8x6, 1x4 & 1x6
WP4: 1x6, 1x8

Glue: Waterproof synthetic resin, Type I vinyl emulsion
Cross-linking adhesive. ASTM D5572

Princeton Forest Products
DISCOVER THE BEAUTY OF WOOD

Visit us on the web at: princetonforestproducts.com

Princeton Forest Products • Post Office Box 116 • Orange Industrial Park • Orange, MA 01364 • 1-800-504-8044 • Fax: 978-544-7245

Specifications

Primelock Patterns

Page Two

Decay

Resistance: Moderate decay resistance. The most naturally decay resistant of the white pines. Suitable for exterior use when painted.

Dryness: Kiln dried to 6%-8% moisture content before finger-jointed; equalized at 10%-12% for yard storage.

Dimensional

Stability: Kiln dried.

Surface: Fine-grained, very smooth surface. Difficult to splinter.

Workability: Easily worked with hand or machine tools. Displays details well.

Tallies: All 16' lengths. Custom lengths also available.

Joints: Non-structural horizontal finger-joints.

Coating

System: Multi-layered protection: 3-step process. Condition. Sealer/primer. Topcoat. All applications meet MPI Green Performance™ standards.

Environment

Friendly: Applied by Authorized Primelock® Prestainer.