

SPECIFICATIONS



Species: Pinus strobus

Common Names: Eastern White pine

Brand/Trade

Name: Primelock®

Range Of

Origin: Maine; northeast US; eastern Quebec

Appearance: Uniform texture. Straight-grained. Naturally light in color. Accepts paint well.

Grade: Clear

Patterns: 1/2x6 Bevel Siding
3/4x10 Bevel Siding
1x6 Drop Siding/German Siding
1x6 & 1x8 Nickel Gap

Glue: Waterproof synthetic resin, Type I vinyl emulsion
Cross-linking adhesive. ASTMD5572

Decay

Resistance: Moderate decay resistance. The most naturally decay resistant of the white pines. Suitable for exterior use when painted.

Specifications

Primelock Siding

Page Two

Dryness: Kiln dried to 6%-8% moisture content before finger-jointed; equalized at 10%-12% for yard storage.

Dimensional

Stability: Kiln dried.

Surface: Fine-grained, very smooth surface. Difficult to splinter.
Coating: Consistent finish eliminating brush marks, rack marks, etc. Reversible.

Workability: Easily worked with hand or machine tools. Displays details well.

Tallies: All 16' lengths. Custom lengths also available.

Joints: Non-structural horizontal finger-joints.

Coating

System: Multi-layered protection: 3-step process.
Condition. Sealer/primer. Topcoat. All applications meet MPI Green Performance™ standards.

Environment

Friendly: Applied by Authorized Primelock® Prestainer.