

SPECIFICATIONS



Species: Pinus strobus

Common Names: Eastern White pine

Brand/Trade

Name: Primelock®

Range Of

Origin: Maine; northeast US; eastern Quebec

Appearance: Uniform texture. Straight-grained. Naturally light in color. Accepts paint well.

Grade: Clear

Boards:

S4S
1 x 2 5/4 x 4
1 x 3 5/4 x 5
1 x 4 5/4 x 6
1 x 5 5/4 x 8*
1 x 6 5/4 x 10*
1 x 8* 5/4 x 12*
1 x 10* *Edge glued
1 x 12*

Glue: Waterproof synthetic resin, Type I vinyl emulsion
Cross-linking adhesive. ASTM D5572



Visit us on the web at: princetonforestproducts.com

Specifications

Primelock Boards

Page Two

Decay

Resistance: Moderate decay resistance. The most naturally decay resistant of the white pines. Suitable for exterior use when painted.

Dryness: Kiln dried to 6%-8% moisture content before finger-jointed; equalized at 10%-12% for yard storage.

Dimensional

Stability: Kiln dried.

Surface: Fine-grained, very smooth surface. Difficult to splinter.

Workability: Easily worked with hand or machine tools. Displays details well.

Tallies: All 16' lengths. Custom lengths also available.

Joints: Non-structural horizontal finger-joints.

Coating

System: Multi-layered protection: 3-step process. Condition. Sealer/primer. Topcoat. All applications meet MPI Green Performance™ standards.

Environment

Friendly: Applied by Authorized Primelock® Prestainer.