

SPECIFICATIONS



Species:	<i>Pinus resinosa</i>										
Common Names:	Red Pine, Norway pine										
Brand/Trade Name:	Saco Valley Flooring										
Range Of Origin:	Eastern Quebec, Maine										
Appearance:	Smooth, even texture with firmly fixed knots. Pale reddish tinge to a reddish brown.										
Grade:	Comparable to Sound Tight Knot allowing occasional black fixed knot; no through defect.										
Patterns:	Tongue & Groove Center Match with relief on back. <table><thead><tr><th>Nominal</th><th>Face Width</th></tr></thead><tbody><tr><td>1 x 6</td><td>3/4" x 5 1/8"</td></tr><tr><td>1 x 8</td><td>3/4" x 7 1/8"</td></tr><tr><td>1 x 10</td><td>3/4" x 8 7/8"</td></tr><tr><td>1 x 12</td><td>3/4" x 11" (limited quantities)</td></tr></tbody></table>	Nominal	Face Width	1 x 6	3/4" x 5 1/8"	1 x 8	3/4" x 7 1/8"	1 x 10	3/4" x 8 7/8"	1 x 12	3/4" x 11" (limited quantities)
Nominal	Face Width										
1 x 6	3/4" x 5 1/8"										
1 x 8	3/4" x 7 1/8"										
1 x 10	3/4" x 8 7/8"										
1 x 12	3/4" x 11" (limited quantities)										
Decay Resistance:	Low decay resistance.										
Dryness:	Kiln dried to 6%-8% moisture.										
Stability:	Kiln dried.										
Strength:	Moderately strong and stiff.										

Princeton Forest Products

DISCOVER THE BEAUTY OF WOOD

Visit us on the web at: princetonforestproducts.com

SPECIFICATIONS

Saco Valley Flooring

Page Two

Surface

Hardness: Harder than Eastern White pine; slightly below Southern Yellow pine.

Surface: Fine-grained, very smooth surface. Difficult to splinter.

Other: High resin content. Interior use only. When exposed to sun in exterior application, resin will bleed.

Tallies: 6' to 16' with occasional 4' and 5'.

Installation: Precondition material on site for at least 14 days. Toe nail 1 x 6. Face nail 1 x 8, 1 x 10, and 1 x 12. (Face nail 1 x 6 if installed where conditions reflect variable heat and humidity.) Blunt tip nails reduce splitting. Screws require predrilling. Lightly sand with care. Sweep to settle dust between boards. Wipe with clean cloth to prepare surface for finishing. Select a high quality polyurethane. Follow manufacturers' directions.

Retail

Location: