

Care and Finish

Before beginning any staining we suggest a light sanding of the product with an orbital sander and 110 grit sand paper to aid in stain penetration.

Stain:

If deck boards have not been prestained (see installation tips), apply a protective oil-based stain as soon as possible. Make sure the stain contains:

- 1. UV protection
- 2. Water-repellent preservative
- 3. Mildewcide

A stain with some pigment will be more effective than a completely clear coating. Select a premium penetrating oil stain rather than paint. (Consider a product line that offers a stain for hardwoods for a maximum penetrating formula.) Always follow instructions on a manufacturer's label. Do not use a solid dark stains or paint.

Keep Clean:

Remove dirt on a regular basis with a commercial deck wash or a household recipe of 1 quart bleach, 3 quarts warm water, 2/3 cup TSP, 1/3 cup detergent*. NO AMMONIA. Sand lightly if wood fibers are raised.

Refinish:

Refinish a clean deck on the schedule recommended by the stain manufacturer. If a deck is built in the fall or winter and cannot be stained immediately due to temperatures, plan to clean and finish the deck as soon as possible in the spring.

* A bleach formula is recommended when a mildew or algae is detected.

Take care to cover and protect adjacent vegetation during use.





Installation Tips

Storage: Keep dry by placing blocks under lumber for ventilation.

Do not store directly on the ground. Cover with tarp.

Protect: For maximum performance, pre-stain deck boards and railing components on all sides

prior to installation. Select a premium penetrating oil stain rather than paint. Consider a product line that offers a stain for hardwoods for a maximum penetrating formula.

Seal all end cuts.

Site Preparation: Clear rocks and debris from site. Grade site for proper drainage. Remove vegetation and

lay down landscape paper or poly. Maintain sufficient air flow under deck.

Space: Leave at least 1/8" gap between deck boards.

Predrill: Predrill ends to avoid splitting.

