

Species:	Pinus Strobus.
Common Name:	Eastern White pine.
Brand/Trade Name:	PRIMECLASSIC, Princeton Classic Moulding, Simplicity System™.
Range of Origin:	Northeast US & Eastern Quebec.
Appearance:	Uniform texture. Straight-grained. Naturally light in color. Accepts paint well.
Grade:	Clear, finger-joint.
Patterns:	35 classic moulding patterns fashioned from finger-joint clear pine. Profiles are manufactured with precision tools calibrated to a tolerance of .006". Casings, bases, crowns, back bands, base caps & chair rails. Patterns organized into 6 collections.
Glue:	Waterproof synthetic resin, Type I cross-linking adhesive. ASTM D5572
Decay Resistance:	Moderate decay resistant. The only naturally decay resistant of the pines.
Dryness:	Kiln dried to 10%-12% moisture content.
Dimensional Stability:	Kiln dried.
Surface:	Fine-grained, very smooth surface. Difficult to splinter.
Workability:	Easily worked with hand or machine tools. Displays details well.
Tallies:	Casings, back bands & New Brunswick chair rail: 15' lengths. Bases, crowns, base caps, cottage chair rail & wainscotting: 16' lengths *10' & longer trimbacks
Primer:	Copolymer acrylic emulsion primer. Water based. VOC compliant. Color: flat white. Application: 2 coats applied by curtain paint system with uv drying system - buffed - each coat 2 mil dry. Surface contours buffed for smoothness.
Coating System:	1. Four step patented coating system, formula owned by Princeton Forest Products/Matra. 2. Cross-Linked Copolymer UV Sealer - Scuff Sanded & Water Based 100% Acrylic Top Coat.
Environment Friendly:	Zero VOC.
Installation & Finishing Techniques:	Ideal for all interior applications. For exterior application, adhesive is rated as water proof. Mouldings are double primed with a Patented Coating System Formula owned by Princeton Forest Products / Matra and ready to paint with your choice of latex or oil topcoat.