

Species:	Pinus strobus.				
Common Name:	Eastern White pine.				
Brand/Trade Name:	PRIMELOCK®.				
Range of Origin:	Northeast US & Eastern Quebec.				
Appearance:	Uniform texture. Straight-grained. Naturally light in color. Accepts paint well.				
Grade:	Clear, finger-joint.				
Boards:	S4S	1 X 2	1 X 6	5/4 X 4	5/4 X 10
		1 X 3	1 X 8	5/4 X 5	5/4 X 12
		1 X 4	1 X 10	5/4 X 6	
		1 X 5	1 X 12	5/4 X 8	
Glue:	Waterproof synthetic resin, Type I cross-linking adhesive. ASTMD5572				
Decay Resistance:	Moderate decay resistance. The only naturally decay resistant of the pines. Suitable for exterior use when painted.				
Dryness:	Kiln dried to 10% - 12% moisture content.				
Dimensional Stability:	Kiln dried.				
Surface:	Fine-grained, very smooth surface. Difficult to splinter.				
Workability:	Easily worked with hand and machine tools. Displays detail well.				
Tallies:	All 16' lengths. Custom lengths also available.				
Joints:	Non-structural, horizontal finger-joints.				
Coating System:	<ol style="list-style-type: none"> 1. Four Steps Patented Coating System Formula owned by Princeton Forest Products/ Matra. 2. Cross-Linked Copolymer UV Sealer – Scuff Sanded & Water Based 100% Acrylic Top Coat. 3. Back Stamp and Specific Layer Application to allow moisture to escape. 				
Environment Friendly:	Zero VOC.				
Installation & Finishing Techniques:	Interior and exterior applications. Boards are double primed with a Patented Coating System Formula owned by Princeton Forest Products / Matra and ready to paint with your choice of latex or oil topcoat.				

For proper installation, refer to installation guide at www.princetonforestproducts.com